

Meter enclosures KREPTA 5 IP66

KREPTA 5 Schurn-P IP66 Meter enclosures











- Installation type : surface
- Protection : IP66
- **IK Code** (impact rating): IK08
- Material of box: ABS
- Material of door: PC
- Quantity of modules: 3 – 12
- Working temperature: -40÷80 °C
- Guarantee: 5 years
- Rated amperage, A: 100

- Durable polycarbonate cover.
- Increased IP - not afraid of immersion in water!
- The lugs for fastening to the support are provided by the design.

KREPTA 5 Schurn-P IP66 Meter enclosures, Range

4 SKU

Schurn-P 1/3 IP66 PC IEK	Schurn-P 1/8 IP66 PC IEK	Schurn-P 3/6 IP66 PC IEK	Schurn-P 3/12 IP66 PC IEK
  <p>3</p>	  <p>8</p>	  <p>6</p>	  <p>12</p>

Schurn-P IP66 PC LIGHT IEK

Equipment	KREPTA 5	LIGHT
DIN rail	+	+
Rubber plugs	+	+
Screws and plastic plugs	+	+
Sticker "Electric shock hazard"	+	+
Cabel gland	+	
Busbar N/PE	+	
Marking tape	+	
Packing	colored cardboard	plastic bag

The price is lower than the standard series by



15%

KREPTA 5 Schurn-P IP66

Design features




High protection IP66 due to the presence of a sealing



Possibility of sealing the door (for models ShchURn-P 1/3 and ShchURn-P 3/12) and the enclosure

UV resistance



KREPTA 5 Schurn-P IP66

Design features



Special hinges for quick door removal (removable when the door is open)

Holes for fastening to a support using a mounting tape (except for ShchURn-P 1/3 IP66 PC IEK)



Convenient access to circuit breakers, the ability to install up to 12 circuit breakers

KREPTA 5 Schurn-P IP66

Design features



Break-out holes of various diameters for installing cable glands for different sections at the top and bottom of the enclosures



Dimension extension lines on the back of the enclosures



Installing the meter on a mounting panel or on a DIN rail